



SERMAC EXTREME 5Z41

Pump Specifications

| | |
|----------------------------------|---------------|
| Maximum output | 130 cu.m./hr. |
| Delivery cylinder (hard chromed) | 230 x 2000 mm |
| Strokes per minute | 26 |
| Concrete pressure (head side) | 61 bar |
| Hopper capacity | 600 ltrs |
| S – Tube | 200 x 180 mm |
| Max. aggregate size | 50 mm |

Boom Specifications

| | |
|-------------------------------|-------------------------|
| 5 section Z fold (vert.reach) | 40.8 M |
| Maximum horizontal reach | 36.8 M |
| Unfolding height | 8 M |
| Rotation | 370 degree |
| Section Articulation | 97°/180°/240°/180°/266° |
| Delivery line | 125mm |
| 1 st section | 8.5 M |
| 2 nd section | 6.9 M |
| 3 rd section | 6.9 M |
| 4 th section | 7.25 M |
| 5 th section | 7.25 M |

Standard Features

- Two proportional remotes: Radio remote & Cable remote
- Hopper grate vibrator
- Automatic lubrication system (pumpkit standard, boom system optional)
- End hose 3.6m
- Tool kit
- Outrigger Pads



For NZ to be mounted on 10 x 4 truck, Overweight permit required

Working Diagram

